



EQ-DD4 Digital / LED Counter Display



| Technical Specifications | EQ-DD4 | EQ-DD4W |
|------------------------------|---|----------------|
| No. of Digits | 4 – Numeric (7-Segment - Italic) | |
| LED Color | Red Only Green Only (Optional) Red & Green (Optional) | |
| Brightness | Low / High (Selectable) | |
| Number Flashing | 0 to 100 seconds (Selectable) | |
| Body Color | Dull Black | |
| Housing | Option-1: HS-PVC Option-2: Stainless Steel (Optional) | |
| Mounting | Desktop / Ceiling (Selectable) | |
| Communication Port | RS-485 | RF (Wireless) |
| RF Frequency | - | 800 to 900 MHz |
| Max Wireless Range | - | 100 meters |
| Baud Rate | 9600 / 19200 bps | - |
| ID Range | 01 to 255 | |
| Maximum Devices per Location | 255 | 96 |
| Anti-Hanging Mode | Auto-Reset on Distortion / Malfunction | |
| Dimensions | 230 x 40 x 85 mm (LxWxH) | |
| Storage Temperature | -10° to 75°C | |
| Storage Humidity | 5% to 9% (non-condensing) | |
| Operating Temperature | 5° to 50°C | |
| Power Supply | POC (Power Over Controller) | 12VDC – 500mA |
| Auto ON / OFF | 1. Using Master Control 2. With User Login & Logout | |
| Power Save Mode | Yes | |