



EQ-LDx

Counter LCD Displays

Multi-Function Display

- ✓ Queue System
- ✓ Multimedia Promotions
- ✓ Customer Information
- ✓ Live Dashboard
- ✓ And more



| Technical Specifications – EQ-LDx | | | | | | | |
|--|---|---------|----------|----------------|----------|--------------|-----------|
| Model | EQ-LD7 | EQ-LD8 | EQ-LD10 | EQ-LD12 | EQ-LD15 | EQ-LD17 | EQ-LD19 |
| Display Size | 7" | 8" | 10.2" | 12" | 15" | 17" | 19" |
| Max. Number of Displays (Under Single Control) | Up to 4 / 8 / 16 / 32 / 64 / 96 / 128 / 512 / 1024 / 4096 (Depending upon the Main Control System) | | | | | | |
| Modes of Operation | Multi-Function Capability <ul style="list-style-type: none"> ◆ Counter Display for Queuing System ◆ Multi-Media Promotions (24 Hours / When Idle) ◆ Customer Information ◆ Live System Dashboard (in Supervisor / Manages' Rooms) ◆ Messages / Instructions – (to Secretary / Stores / Pantry / etc.) | | | | | | |
| Display Proportion | 16:9 | 4:3 | | | | | |
| Resolution | 800x480 | 800x600 | 1024x600 | 800x600 | 1024x768 | 1280x1024 | 1280x1024 |
| Response Time | 50 to 100 Milliseconds | | | | | | |
| Effective Visible Angle | 120° L / 120° R | | | | | | |
| Available Storage Memory | Standard 4GB (Upgradeable to 32GB) | | | | | | |
| Communication | USB & Wi-Fi Cabled Ethernet (Optional) Bluetooth (Optional) GSM / 3G (Optional) | | | | | | |
| Audio | Built-in Stereo Speakers (with MP3 / WMA play option) | | | | | | |
| Pictures / Video Option | JPG / JPEG / MPEG1 / MPEG 2 / MPEG 4 / AVI | | | | | | |
| Languages | English, French, German, Italian, Spanish, Arabic, Portuguese & Dutch | | | | | | |
| Storage Temperature | -20°C to 60°C | | | | | | |
| Storage Humidity | 20% to 80% (Relative) | | | | | | |
| Operating Temperature | 5°C to 40°C | | | | | | |
| Power Supply | 5V DC 1 AMP | | | 12V DC 1.5 AMP | | 12V DC 2 AMP | |