

EQ-LDx Smart LCD Displays

Multi-Function:

- ✓ Counter Display (Queue System)
- ✓ Multimedia Play-List
- ✓ Customer Information
- ✓ Corporate Messaging
- ✓ In-house Promotions
- ✓ 3rd Party Advertisements
- ✓ Live Dashboard
- ✓ And more





| Technical Specifications – EQ-LDx | | | | | | | |
|-----------------------------------|--|-----------|---|---------|----------|-----------|-----------|
| Model | EQ-LD7 | EQ-LD8 | EQ-LD10 | EQ-LD12 | EQ-LD15 | EQ-LD17 | EQ-LD19 |
| Display Size | 7" | 8" | 10.2" | 12" | 15" | 17" | 18.5" |
| Max. Number of Displays | Up to 4 / 8 / 16 / 32 / 64 / 96 / 128 / 512 / 1024 / 4096 | | | | | | |
| (Under Single Control) | (Depending upon the Main Control System) | | | | | | |
| OS | Android (Standard) / Linux (Optional) | | | | | | |
| Modes of Operation | Counter Display for Queue Management System Multi-Media Promotions (Pre-Defined Schedule or for 24 Hours) Customer Information (Service Areas / Lobbies / Elevators, etc.) | | | | | | |
| (Multi-Function | Live Dashboard (For Supervisors / Managers) | | | | | | |
| Capability) | | | ructions (to Specific or All Departments) | | | | |
| | In-house Promotions (Videos / Pictures / Messages) | | | | | | |
| | ♦ 3 rd Party Advertisements (Revenue Generation) | | | | | | |
| Display Proportion | 16:9 4:3 | | | | | | |
| Resolution | 800x480 | 800x600 | 1024x600 | 800x600 | 1024x768 | 1280x1024 | 1280x1024 |
| Response Time | 50 to 100 Milliseconds | | | | | | |
| Effective Visible Angle | 120° L / 120° R | | | | | | |
| Available Storage Memory | Standard 4GB (Upgradeable to 32GB) | | | | | | |
| Communication | Standard > USB & Wi-Fi Optional > Ethernet / PoE (EQ-LD10 & above) / Bluetooth / 3G / NFC | | | | | | |
| Audio | Built-in Stereo Speakers (with MP3 / WMA play option) | | | | | | |
| Pictures / Video Option | JPG / JPEG / MPEG1 / MPEG 2 / MPEG 4 / AVI | | | | | | |
| Languages Supported | English, French, German, Italian, Spanish, Arabic, Portuguese & Dutch | | | | | | |
| Storage Temperature | -20°C to 60°C | | | | | | |
| Storage Humidity | 20% to 80% (Relative) | | | | | | |
| Operating Temperature | 5°C to 40°C (Ideal Temp. = Between 20°C to 25°C) | | | | | | |
| Power Supply | 5 | V DC 1 AN | /IP | 12V DC | 1.5 AMP | 12V DC | 2 AMP |
| Life Span | 40,000 to 60,000 Hours [Approximately 4 to 7 Years] (Life Span may vary depending upon the Environmental Conditions including | | | | | | |

Operating Temperature, Humidity, Power Stability, Exposure to Sunlight, etc.)







STEP ON IT