



EQ-TD09x

Smart TOKEN DISPENSER

Multi-Purpose! Can be used as:

- ✓ Independent Token Dispenser (Direct)
 - ✓ Main Control / Queue Server & Token Dispenser
 - ✓ Master Dispenser (Integrated with Queue Server)
 - ✓ Slave Dispenser (Integrated with Queue Server)
 - ✓ Queue Token Dispenser + C.F.S.
 - ✓ C.I.F.S. (Customer Information & Feedback System)
 - ✓ Online Queue Token Booking Retrievals
 - ✓ Meeting Rooms Booking Management
- ... and more**



Technical Specifications – EQ-TD09x

Screen Size	10.1-inch	11-inch	13.3-inch	15.6-inch
Display Type	Std. LED		IPS LED	
Visible Angle	140°/140°		170°/170°	
Resolution	1024x600		1280 x 800	1920 x 1080
Max. Number of Units	Up to 65,536 under Single Control (Depending upon No. of Channels for the Central Mgmt. Software)			
OS	Option-1: Android Based (2GB/32GB)			
	Option-2: Windows Based (i3/4GB/1TB)			
Modes of Operation (Multi-Function Capability)	<ul style="list-style-type: none"> ◆ Independent Token Dispenser (Direct Token Issuance Only) ◆ Main Control System (Queue Server) + Standard Token Dispenser ◆ Master Token Dispenser (Integrated with the Queue Server) ◆ Slave Token Dispenser (Integrated with the Queue Server) ◆ Queue Token Dispenser + C.F.S. (Customer Feedback System) ◆ Queue Token Dispenser + C.I.S. (Customer Information System) ◆ C.I.F.S. (Customer Information & Feedback System) ◆ Online Booking Management (Queue-Booking) ◆ Queue Token Booking Retrieval System ◆ Meeting Rooms Management (Check Availability & Booking) ◆ Conference Rooms / Classrooms Booking Management And more 			
Communication Ports	Ethernet (Wi-Fi = Optional)			
Supported Languages	English, French, German, Italian, Spanish, Arabic, Portuguese, Dutch and more...			
Storage Temperature	-20°C to 60°C			
Storage Humidity	20% to 85% (Relative)			
Operating Temperature	5°C to 45°C (Ideal Temp. = Between 15°C to 35°C)			
Power Supply	24V DC 2 AMP			
Life Span	40,000 to 50,000 Hours [Approximately 7 to 8 Years] (Life Span may vary depending upon the Environmental Conditions)			